

Art Peel SUL

Product Description

Art Peel SUL is a 160gsm bright white, repositionable wall adhesive. It's not your average printable wall fabric; it's designed to bring your art to life through outstanding print quality, deep, rich colors, and crisp resolution that your art deserves. Use it for wall graphics, wall murals, stickers, labels, and anything else your creativity allows. Art Peel is compatible with high-quality aqueous inks.



Physical Specifications

Material Type	100% Polyester-woven fabric
Basis Weight	160 gsm
Caliper	7 mil
Surface	Matte
Texture	Fine weave
Opacity	80%
Gloss (@60°)	2
Whiteness	.93
Adhesive	Removable

Printer Compatibility & Handling

Eco Solvent Printer Compatibility	Epson®, Mutoh®, Roland®, HP Seiko®, Mimaki®
	View Comprehensive List Online
True Solvent Compatibility	Mimaki®, Mutoh®, HP Seiko®
Grand Format Solvent Compatibility	Gandi®, HP Scitex®, Inca®, Nur®
UV Printer Compatibility	HP Scitex®, Mimaki®, Vutek®
Ink Compatibility	EcoSol and high-grade solvent inks, Latex inks, and UV inks
Optimal Print Environment	70°F (21°C), 30-60% Relative Humidity
Handling:	Avoid touching the coated surface. Cotton gloves should be used when handling inkjet coated materials from Breathing Color. Note: coated surface of every roll faces out.

Additional Information

Storage	70°F (21°C) / 50% Relative Humidity; store in original packaging and in a controlled environment
Shelf Life	Minimum 1 year from purchase date, when stored as specified
Lamination	Not required, but always highly recommended by Breathing Color
Print Settings & ICC Profiles	Custom ICC Profile will produce optimum results

Note: Actual print stability will vary according to media, printed image, display conditions, light intensity and atmospheric conditions. Breathing Color does not guarantee the longevity of prints. For maximum print life display all prints under glass or lamination or properly store them. All of the descriptive information and recommendations for the use of Breathing Color products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by Breathing Color. All purchasers of Breathing Color products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss of damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.

Art Peel SUL Blockout

Product Description

Art Peel SUL Blockout is a 180gsm bright white, repositionable wall adhesive. It's not your average printable wall fabric; it's designed to bring your art to life through outstanding print quality, deep, rich colors, and crisp resolution that your art deserves. Use it for wall graphics, wall murals, stickers, labels, and anything else your creativity allows. Art Peel is compatible with high-quality aqueous inks.



Physical Specifications

Material Type	100% Polyester-woven fabric
Basis Weight	180 gsm
Caliper	7 mil
Surface	Matte
Texture	Fine weave
Opacity	99%
Gloss (@60°)	2
Adhesive	Removable

Printer Compatibility & Handling

Eco Solvent Printer Compatibility	Epson®, Mutoh®, Roland®, HP Seiko®, Mimaki®
	View Comprehensive List Online
True Solvent Compatibility	Mimaki®, Mutoh®, HP Seiko®
Grand Format Solvent Compatibility	Gandi®, HP Scitex®, Inca®, Nur®
UV Printer Compatibility	HP Scitex®, Mimaki®, Vutek®
Ink Compatibility	EcoSol and high-grade solvent inks, Latex inks, and UV inks
Optimal Print Environment	70°F (21°C), 30-60% Relative Humidity

Handling: Avoid touching the coated surface. Cotton gloves should be used when handling inkjet coated materials from Breathing Color. **Note:** coated surface of every roll faces out.

Additional Information

Storage	70°F (21°C) / 50% Relative Humidity; store in original packaging and in a controlled environment
Shelf Life	Minimum 1 year from purchase date, when stored as specified
Lamination	Not required, but always highly recommended by Breathing Color
Print Settings & ICC Profiles	Custom ICC Profile will produce optimum results

Note: Actual print stability will vary according to media, printed image, display conditions, light intensity and atmospheric conditions. Breathing Color does not guarantee the longevity of prints. For maximum print life display all prints under glass or lamination or properly store them. All of the descriptive information and recommendations for the use of Breathing Color products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by Breathing Color. All purchasers of Breathing Color products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss of damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.