



Belgian Linen
BY BREATHING COLOR

Product Description

Belgian Linen is a unique European textile which is grown, harvested, and woven entirely in Belgium by members of the Masters of Linen & European Flax Charter Associations. It has been prized for thousands of years for the high quality, softness, and durability it offers. It naturally has a rich color absorption and is lint-free and hypoallergenic. This is why Belgian Linen is widely known as the world's finest linen available.

Breathing Color combines this remarkable material with our advanced ink receptive coating technology, resulting in the highest-quality inkjet textile available on the market.



Physical Specifications

Material Type	Belgian Linen
Basis Weight	425 gsm
Caliper	18 mil
Gloss	2
Whiteness	.90

Additional Information

Storage	70°F (21°C) / 50% Relative Humidity; store in original packaging and in a controlled environment
Shelf Life	Minimum 1 year from purchase date, when stored as specified
Lamination	Not required
Print Settings & ICC Profiles	Custom ICC Profile will produce optimum results

Note: Actual print stability will vary according to media, printed image, display conditions, light intensity and atmospheric conditions. Breathing Color does not guarantee the longevity of prints. For maximum print life display all prints under glass or lamination or properly store them. All of the descriptive information and recommendations for the use of Breathing Color products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by Breathing Color. All purchasers of Breathing Color products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss of damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.

Printer Compatibility & Handling

Aqueous Piezo Printer Compatibility	Epson®, Roland®, Mutoh®, Mimaki® View Comprehensive List Online
Aqueous Thermal Printer Compatibility	Canon®, HP®, ColorSpan®, Encad Novajet®
Solvent Printer Compatibility	N/A
Ink Compatibility	Aqueous Pigment and Dye
Optimal Print Environment	70°F (21°C), 30-60% Relative Humidity

Handling: Avoid touching the coated surface. Cotton gloves should be used when handling inkjet coated materials from Breathing Color. **Note:** coated surface of every roll faces out.